

# TITANIUM D2

# SAE 5W-30

## Full Synthetic Engine Oil

### Description

Omicraft Titanium D2 5W-30 is a full synthetic high-performance mid-SAPS engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Emission Reduction Systems in both petrol and diesel vehicles.

### Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction Systems in both petrol and diesel vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both petrol and diesel engine passenger car and light commercial vehicles.

### Applications

Omicraft Titanium D2 5W-30 has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with the latest Diesel Particulate Filters, and all petrol catalytic converters.

Omicraft Titanium D2 5W-30 offers excellent performance at both very low and very high operating temperatures, and long term engine protection from wear sludge and deposit build-up.

Omicraft Titanium D2 5W-30 has the General Motors Service Fill **dexos2™** approval, which is required for all GM/Holden petrol and diesel models from 2010. GM/Holden have advised that **dexos2™** specification is backward compatible to older GM/Holden specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Holden petrol and diesel vehicles can use **dexos2™** lubricants.

### Specifications and Approvals

Omicraft Titanium D2 5W-30 meets or exceeds the requirements of: API SM, ACEA C3, **dexos2™** (License No.: D20665HJ179).

Omicraft Titanium D2 5W-30 is recommended for use in applications requiring: General Motors Service Fill **dexos2™**.



Available in 5L, 20L and 208L sizes from Ford Trade Club